

# Construction of the New Safety Interlock System for SPring-8 Accelerator

C. Saji, H. Hanaki, S. Hashimoto, Y. Hashimoto, M. Kago, K. Kawata, T. Masuda, T. Matsushita, S. Miyamoto, T. Nagaoka, N. Nariyama, H. Ohkuma, K. Soutome, S. Suzuki, M. Takao, R. Tanaka, M. Toko, Y. Tsuzuki, A. Yamashita, H. Yonehara

Japan Synchrotron Radiation Research Institute(JASRI/SPring-8)

15<sup>th</sup> Apr., 2010, O-45

The 7<sup>th</sup> international Workshop on Accelerator Operations

# Contents

- Motivation
- Introduction
  - Accelerator
  - Accelerator Safety Interlock System
- Requirement
- New conceptual design
- Construction
- Summary

# Motivation

- Current safety interlock system for SPring-8 accelerator has complicated safety logic and equipment components.
  - Problems:
    - Take many cost (person, time) for safety inspection
    - **Very difficult to expand the system for additional accelerator**  
etc..
- Construction of new safety system is difficult
  - Tight schedule for short shutdown time
  - Should continue accelerator operation  
between each construction  
etc..

But...


- We will **change conceptual design** of safety system .

# Introduction

- Accelerator components
  - Linac(Li)
  - Synchrotron Booster(Sy)
  - Storage Ring(SR)
  - NewSUBARU storage ring(NS)
- Non-accelerator area:
  - L3 beam-transport (L3)

SPring-8:

Electron beam  
8-GeV Storage Ring



## - New Accelerator, XFEL/SPring-8:




XFEL

- Under construction
- 8-GeV LINAC
- will start operation on 2011

©RIKEN/JASRI

- New Accelerator, XFEL/SPring-8:



# Accelerator Components

## - Five access controlled areas:

Linac(Li)

Synchrotron Booster(Sy)


Storage Ring(SR)

L3 beam-transport (L3)

NewSUBARU storage ring(NS)

Accelerator/non-accelerator area

Gun/RF



## - Division of area:

Beam shutters

▲ Beam shutter

## - Beam generation/acceleration:

- One electron gun (GUN)
- Four acceleration RFs.


SPring-8 Accelerator Components





# Various Accelerator Operations (2)

NS injection operation →



Possible to enter SR machine tunnel

SPring-8 Accelerator Components


# Various Accelerator Operations (3)

SR/NS injection  
switching operation



Destination is switched  
by changing  
one Bending Magnet status

This BM is **ON**  
→ Transport to **SR**





# Accelerator Safety Interlock System

Safety Interlock System (= Personnel Safety System)

Purpose:


Protect persons from radiation hazard  
induced by electron beams and synchrotron radiation

Basic Function:

- Monitoring safety equipment:  
radiation monitor etc..
- Access control:  
manage permission for entering  
radiation-controlled areas
- Control electron beam :  
manage permission of **GUN** and **RF**  
as safety conditions

System:

- Programmable Logic Controller (PLC)  
based system
- Consist of **several PLC systems**




Accelerator safety interlock system  
Main racks

# Current Accelerator Safety Interlock System (1)

## Accelerator Area Interlock system:

Five acc. areas managed by  
Four area interlock systems



Spring-8 Accelerator Components

Permissions

# Current Accelerator Safety Interlock System (2)


## Operation Mode Interlock System:

→ manage combination of areas

• Area system information integrated to MODE interlock system

• **MODE judges** safety of area combination and give permissions.

→ Status of safety equipment(HW)



Current Accelerator Safety Interlock System

Operation Mode management system



Complicated safety Logic  
Lower independency of acc. areas  
→ Hard to maintain, modify and troubleshoot

# Current Accelerator Safety Interlock System (3)

## The number of Operation mode (MODE)

At the beginning (1997~),  
Accelerator components were  
Li, Sy and SR.

- The number of **MODE** has increased as accelerator upgrade
  - L3 beam-transport added
  - NS storage-ring added
  - Topup operation started
  - Destination switching operation started

→ The number of MODEs drastically increased

- Complicated operation
- Very difficult to upgrade system (for additional accelerator)

Safety interlock has MODEs explicitly

## List of operation mode (part)

- READY Mode
- L2 Mode
- Sy-injection Mode
- SR-injection Mode
- SR-storage Mode
- L3 Mode
- Topup Mode
- NS-injection Mode
- NS-storage Mode
- Sy • NS-injection Mode
- SR • NS-injection Mode
- Topup • NS-injection Mode
- L2 + Sy-storage Mode
- L2 + Sy-storage + SR-storage Mode
- L2 + Sy-storage + NS-storage Mode
- L2 + Sy-storage + SR-storage + NS-storage Mode
- Sy-injection + SR-storage + NS-storage Mode
- Topup + NS-storage Mode
- NS-injection + Sy-storage + SR-storage Mode
- SR-storage + NS-storage Mode
- L3 + Sy-storage Mode
- L3 + Sy-storage + SR-storage Mode


Around  
60 modes

⋮  
⋮  
⋮

# Requirements for new system

- Easy maintenance  
Many MODEs → internal safety inspection(twice in a year)  
~20 person x 5 days x 2 times
- Easy modification  
Local modification can affects all of system.
- Simple/easy operation  
Many MODEs and complicated safety logic  
can cause operation mistake

- High extendibility



Plan: SPring-8 and XFEL  
Combined operation

XFEL

~60 MODEs → ~120 MODEs?? for additional accelerator.



Need new conceptual design



# New conceptual design

A change of safety Interlock conceptual design  
affects to various division.  
→ need cooperation of several division

## New task force formed:

- Experts in each division was gathered,  
Accelerator Interlock system  
Accelerator operation  
Safety office  
and discussed various issue (2005 ~)



New Conceptual design


Area management system

# New accelerator safety interlock system

## Area management system:

→ Status of safety equipment

■ Permissions



- ~60 MODEs → 0 MODE
- Safety inspection: expected 5days → 3days


- Acc. area managed by Independent system.
  - Li-Sy system divided to three system (GUN, Li, Sy)
- Permissions (GUN/RF) managed by independent system.
- Acc. area system only communicates with GUN system.
- Communication signal will be **one way direction** from acc. system to GUN system.

# New accelerator safety interlock system

## Area management system:

→ Status of safety equipment

■ Permissions



- easy to expand for an additional accelerator

# Construction (1)

## What should we do:

### Construction

- Make/settle additional safety equipment
- Make new safety logic and their software for PLCs  
(for 6 systems)
- Status monitoring/display system
- Wiring/Re-wiring (Signal/Power/Network)
- Rack replacement

### For starting accelerator operation

- Internal safety inspection.
- Official safety inspection (with external inspectors)  
→ should be passed

**- Many things to do  
(SPring-8 has large and many facilities)**


# Construction (2)

(e.g. 2008FY)

## Typical Schedule of Accelerator Operation

2008

2009



Winter shutdown

Summer shutdown

Operation  
 Shutdown  
 Possible to construct

**- Short shutdown period**  
**- a few chance (twice in a year)**  
**→ Construction is difficult for tight schedule**

# Construction schedule in the past and future

Current  
safety  
logic  
running

2007:  
Summer  
Winter

- New equipment developed
- New rack developed

Many modification already  
done in this 3 years.  
**Continue acc. operation.**  
**Keep current safety logic**

2008:  
Summer  
Winter

- Wiring/Re-wiring performed

- Status monitoring/display system developed/setup
- New equipment developed

2009:  
Summer  
Winter

- Two racks replaced

- Wiring/Re-wiring performed
- New equipment developed/setup
- Additional rack developed

New safety logic  
software developed

We are here

# Construction schedule in the past and future

Current safety logic running

2007:  
Summer  
Winter

- New equipment developed
- New rack developed

Many modification already done in this 3 years.  
**Keep current safety logic**  
**Continue acc. operation.**

2008:  
Summer  
Winter

- Wiring/Re-wiring performed
- Status monitoring/display system developed/setup
- New equipment developed

2009:  
Summer  
Winter

- Two racks replaced
- Wiring/Re-wiring performed
- New equipment developed/setup
- Additional rack developed

New safety logic software developed

We are here


New safety logic

2010:  
Summer


- Replace Main two rack and final wiring
- Remove MODE system
- **Install new safety logic, safety inspections**

# Items already prepared


New Control Panel



Status display



New equipment



Old → New


Rack replacement





# Rack replacement (1) – Motivation -

## Motivation:



Current system:

PLC system:

- Li-Sy (one system)

Signal Cable/terminal-block:

- Mixture of Li, Sy, GUN



New system:

PLC system:

- GUN, Li, Sy (3 system)


Signal Cable/terminal-block:

- Independent of Li, Sy, GUN

What to do:

- More rack space
- Replace and rewiring
  - Cables
  - Terminal blocks

# Rack replacement (2) – Procedure-





# Summary

- Current accelerator safety interlock system is complicated.
- Difficult to upgrade interlock system for additional accelerator area.
- **New conceptual design** was settled on.
  - based on **Area management system**
- A part of construction was already finalized with keeping current safety logic.
- **New system will be ready in this end of September and operation will be started.**
  - also ready for expand of an additional accelerator area.

# Supplement

- Accelerator components for SPring-8:



©RIKEN/JASRI

| <b>Interlock System</b> | <b>Covered Area</b> | <b>Related Permission</b>       |
|-------------------------|---------------------|---------------------------------|
| Mode                    | -                   | GUN, Li-RF, Sy-RF, SR-RF, NS-RF |
| Li-Sy                   | Li, Sy              | GUN, Li-RF, Sy-RF, SR-RF        |
| L3                      | L3                  | GUN, NS-RF                      |
| SR                      | SR                  | GUN, SR-RF, Sy-RF               |
| NS                      | NS                  | GUN, NS-RF                      |


**Covered area and related permission of Current Accelerator Safety Interlock System**

| <b>Interlock System</b> | <b>Covered Area</b> | <b>Related Permission</b> |
|-------------------------|---------------------|---------------------------|
| Gun                     | -                   | GUN                       |
| Li                      | Li                  | GUN, Li-RF                |
| Sy                      | Sy                  | GUN, Sy-RF                |
| L3                      | L3                  | GUN                       |
| SR                      | SR                  | GUN, SR-RF                |
| NS                      | NS                  | GUN, NS-RF                |

**Covered area and related permission of New Accelerator Safety Interlock System**  
(Covered areas and related permissions is independently managed by each interlock systems)

# エリア管理(1)

## — エリア・インターロックシステム —



基本の構成・動作は  
全エリア同様


運転モード  
選択不要

RF許可: RF運転許可(蓄積可能)  
GUN許可(エリア): エリアへの入射許可



# エリア管理(2)


## — GUN・インターロックシステム —



# Accelerator Safety Interlock System (3)

## Operation mode(MODE)

- For accelerator operation , appropriate MODE should be selected.
- Several MODEs can be selected
- A MODE including combination of some areas
- MODE transition procedure is complicated.



Operation mode transition

(Red region shows Mode with switching a destination)